

ROLLE 8



TWMima

Packaging Systems

ROLLE 8 IS DURABLE AND EASY TO USE

When the most important criteria are ease of use and robust machine, Rolle 8 is ideal for these applications.

Fast and easy to use


- 1 Wrapping can be started by selecting light or strong wrapping and then start.
 - If necessary, wrapping can be interrupted for the palletisation of products by means of the pause function.

The film can be conveniently adjusted

- 2 The film tension can be adjusted by means of a separate brake roller.
 - A change in the diameter of the film roll does not affect the film tension in the product pallet.
 - The film roll is easy to change.
 - The brake roller can be released to make it easier to fix the film in the product pallet.
 - The height of the product pallet is detected by means of a photocell.

Turntable

- 3 The rotating of the turntable is controlled by a frequency controller. This reduces mechanical stress and the need for maintenance.
 - Thanks to the stepless control of the rotational speed and the smooth start-up of the machine, it is also possible to wrap unstable product pallets.
 - The turntable always stops in the same place. This makes it possible to use a ramp, which is available as an option.



Technical data

Power supply	220–240V / 50 Hz	Rotation speed	1–11 rpm
Machine dimensions	2575 x 1650 mm	Max pallet load dim.	1200 x 1000 mm
Max height	3000 mm	Wrapping height	50–2600 mm
Turn table Ø	1650 mm	Max. pallet load weight	1200 kg
Turn table height	80 mm	Film reel Ø	<260 mm
Weight	360 kg		



Rolle 8 fits into a small space and is easy to transport and install.

